

Economy Class Price First Class Features



3-wheel

GO-GO[®]
ULTRA X



4-wheel

The **Go-Go[®] Ultra X** is loaded with features such as one-hand disassembly and a convenient drop-in battery box for worry-free travel. With a 260 lb. weight capacity, a maximum speed up to 4 mph, a per-charge range up to 6.9 miles on the 3-wheel and 7.2 miles on the 4-wheel, Go-Go[®] Ultra X is an exceptional value.



Feather-Touch Disassembly

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

pridemobility.com



Specifications 3W: S40X 4W: S44X

Weight Capacity	260 lbs.
Maximum Speed ¹	Up to 4 mph
Ground Clearance ²	3W: 3.1" at deck, 1.3" at transaxle, 0.67" at anti-tip 4W: 3" at deck
Turning Radius	3W: 33" 4W: 44"
Overall Length ²	3W: 37" 4W: 39.5"
Overall Width ²	19.5"
Seat-to-Deck Height	15.75"-17.25"
Seat-to-Ground Height	18.25"-20.25"
Front Tires	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear Tires	2.5" x 8" solid
Range Per Charge ^{1,4}	3W: Up to 6.9 miles 4W: Up to 7.2 miles
Total Weight Without Batteries	3W: 76 lbs. 4W: 80 lbs.
Heaviest Piece When Disassembled	3W: 29 lbs. (front section) 4W: 34 lbs. (front section)
Standard Seating	Type: Foldable, compact, vinyl-covered, molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17" Depth: 17"
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	Size: (2) 12 AH, 9 lbs. each Weight: 12 AH: 20 lbs. per battery pack
Battery Charger	Off-board, 2 amp
Colors	 Red

Features

- Convenient dual voltage charger can charge battery pack on-board or off-board
- Feather-touch disassembly permits simple frame separation with only one hand and easily disassembles into five super lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Pride's exclusive black, non-scuffing tires

Accessories

- Cane/crutch holder (single, double)
- Cup holder
- Double crutch holder
- Forearm crutch holder
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger

Options

- Battery pack

Military Patches





Find a compatible lift for your vehicle online:
PRIDEMOBILITY.COM/LIFT-FINDER

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

HCPCS Code: K0899

POWER MOBILITY DEVICE, NOT CODED BY DME PDAC
OR DOES NOT MEET CRITERIA

(US) 800-800-8586

(CAN) 888-570-1113

pridemobility.com



Pride[®]
Mobility Products Corp.